

## SALES PROPOSAL WORKSHEET TANDEMATIC FULL WIDTH DECURLING SYSTEM (PRODUCT KEY N)

SEND PROPOSAL TO:

CUSTOMER:

EMAIL:

ADDRESS:

TEL:

PREPARED BY:

The President's Award  
for Exporting Excellence

ATTENTION:

DATE:

ITEM	DESCRIPTION	APPROX PRICE USD	SELECTED FOR PROPOSAL	
			YES	NO
	STANDARD EQUIPMENT:			
A	FULL WIDTH DECURLER MODEL FWUS ( )-1500 DECURLER FOR REMOVING SMALL CURL (<50 MM), WITH MOUNTING ADAPTORS	9,500		
	OPTIONAL:			
B	PRODUCT KEY D: MH53U DECURLERS AHEAD OF WET-OUT, WITH UHMW SLIDE MOUNTING BASES FOR MANUAL POSITIONING OF DECURLERS	3,000		
<b>REQUIRED, TO BE SUPPLIED BY BUYER:</b>				
C	FULL WIDTH SUPPORT MEMBER ON WHICH TO MOUNT SLIDE BASES FOR DECURLERS			

### INFORMATION REQUIRED FROM CUSTOMER TO PREPARE FORMAL PROPOSAL

- 1) PHOTOS AND SKETCH SHOWING ROLL ARRANGEMENT AND FABRIC PATH AHEAD OF SQUEEZE ROLLS
- 2) MAXIMUM FABRIC WIDTH: \_\_\_\_\_ MM (MUST BE 2500 MM OR LESS)
- 3) MINIMUM FABRIC WIDTH: \_\_\_\_\_ MM (MUST BE NO MORE THAN 1500 MM LESS THAN MAXIMUM FABRIC WIDTH)
- 4) DISTANCE BETWEEN MACHINE SIDE PLATES: \_\_\_\_\_ MM
- 5) AMOUNT OF CURL EXPECTED IN FABRIC AFTER WET-OUT: \_\_\_\_\_ MM  
(IF MORE THAN 50 MM CURL, WE RECOMMEND OPTION B ABOVE IN ADDITION TO FULL WIDTH DECURLER)